

- Venturi type in line inductor with built in by-pass.
- Manufactured in very light and strong E-LITE material.
- Fixed proportioner (3 and 6% standard).
- Check valve to prevent contamination of the foam concentrate.
- Tested with the range of VIPER SG and VIPER CG nozzle to ensure correct operation.



BYPP-7515 360 lpm

INDUCTOR:

1-1/2" BSP Fixed thread
Weight: 800 g.
Length: 14,5 cm.
3 and 6% proportioning standard
1 and 2% available

BYPP-1550.115 lpm

INDUCTOR:

1" BSP Fixed thread
Weight: 950 g.
Length: 17,5 cm.
3 and 6% proportioning standard
1 and 2% available

BYPP-3012.230 lpm

INDUCTOR:

1-1/2" BSP Fixed thread
Weight: 800 g.
Length: 14,5 cm.
3 and 6% proportioning standard
1 and 2% available

FLOW RATE TABLE

Model	Inlet pressure		Flow rate		Loss of pressure	
	psi	bar	gpm	lpm	Foam	By-pass
BYPP - 1560	100	7	18	70	39%	7%
	150	10	23	86	39%	7%
BYPP - 3012	100	7	46	175	33%	14%
	150	10	56	214	33%	14%
BYPP - 7515	100	7	92	350	30%	15%
	150	10	113	429	30%	15%